





Nozzle	EZ	S-HD	A-HD	A-HD	Swirl Cap	Spiral & Fan
Key Attributes	Single orifice, straight through	Single & Dual orifice, right angle	Single orifice, straight through	2, 3, and 4 orifice, straight through	N/A	N/A
Module Compatibility	MOD-Plus	MOD-Plus	MOD-Plus	MOD-Plus	MOD-Plus Swirl Hand Applicator Swirl	MR1300
Construction Material	Brass, Viton seal	Brass with stainless steel inserts, steel fasteners	Brass	Brass	Brass	Brass
Nozzle Orifice Sizes	.010, .012, .015, .020, .025, .030, .035, .040	1 Orifice: .010, .015, .020, .025, .030, .040, .060 2 Orifice: .010, .015, .020, .025, .030 @ angles of 15°22°, 30°, 45°, 60°, 90°	.008, .010, .012, .015, .018, .020, .025, .030, .035, .040, .060	2 Orifice: .010, .015, .020, .025, .030 @ angles of 15°, 22°, 30°, 45°, 60°, 90° 3 Orifice: .010, .015, .020, .025 @ angles of 15°, 22°, 30°, 45° 4 Orifice: .015, .020, .025	.035, .040 @ angles of 15°, 20°, 25°, 30°, 35°	.012 to .052

Nozzle	Straight Through .594 Long	Straight Through 1.0 & 1.5 Long	Straight Through for Multi-Line Nozzles	Extended Module & Swirl
				
Key Attributes	Single orifice, straight through, 3/8-24 Thd	Single orifice, straight through, 3/8-24 Thd	Single orifice, straight through, 8-32 Thd	.90 and 1.50 length, straight through
Module Compatibility	MR1300	MR1300	MR1300	MOD-Plus Extended Module, Swirl Module or Hand Applicator
Construction Material	Brass with stainless steel insert	Stainless steel	Stainless steel	Brass, Viton seal - or - Steel, Viton seal
Nozzle Orifice Sizes	.012, .014, .016, .018, .020, .030, .040, .062	.020, .030, .040, .062	.010, .012, .016, .020, .025, .030, .040, .062	Brass: .90 Noz: .015, .020, .025, .030, .040, .055, .070, .093 Brass or Steel: 1.5 Noz: .010, .015, .020, .025, .030, .040, .070